

LOL-ACC-0215

Model No	LOL-ACC-0215
Application	Accent
Name	Die Cast Aluminium Uplight
Description	LOL-ACC-0215 is a die-cast, copper-free aluminum fitting with a durable powder coat finish for strength and reliability. The housing is equipped with a silicone O-ring to protect against moisture and dust. A clear, tempered, shock and heat-resistant, soda-lime glass lens safeguards the lamp and optics.
Power Input	12V AC, 24V DC
Lamp details	MR16
Power Usage	varies with lamp, 3W to 7W
Beam Angles	varies with lamp, 10 to 120 degrees
Colour Temperature	varies with lamp, 2700k to 3000k
Lumen	varies with lamp
CRI	varies with lamp, 80+ - 90+
Dimming System	Call to discuss
IP	
Finish	Black, Bronze, Textured Rust, Textured Natural Green
Mounting	Spike, surface or tree mount with tree mount kit*
Dimensions	149L x 66 Ø x 77H
Product Notes	* spike included, tree mount junction box or wall mount canopy options available

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

