

LOL-ACC-0287

|                           |   |
|---------------------------|---|
| <b>Model No</b>           | LOL-ACC-0287  |
| <b>Application</b>        | Accent  |
| <b>Name</b>               | Axially Symmetrical Flood   |
| <b>Description</b>        | <i>This compact flood produces a light distribution which is axially symmetrical with a good range of beam angle options. The compact 'bocce' style body is sturdy and corrosion resistant.</i> |
| <b>Power Input</b>        | 240V  |
| <b>Lamp details</b>       | LED Module, LED Module  |
| <b>Power Usage</b>        | 14W, 25W, 40W, 55W  |
| <b>Beam Angles</b>        | 14 & 25W - 8, 13, 22, 47,<br>40&55W - 11, 16, 26, 52  |
| <b>Colour Temperature</b> | 2700k, 3000k, 4000k, 5000k  |
| <b>Lumen</b>              | varies with options   |
| <b>CRI</b>                | 80+   |
| <b>Dimming System</b>     | call to discuss   |
| <b>IP</b>                 | IP65  |
| <b>Finish</b>             | RAL9005 Black Powdercoat<br>Aluminium, RAL9006 Grey<br>Powdercoat Aluminium,<br>RAL9016 White Powdercoat<br>Aluminium   |
| <b>Mounting</b>           |   |
| <b>Dimensions</b>         | 125Ø x 163W x 154H  |
| <b>Product Notes</b>      |   |

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

