

LOL-ACC-0407

Model No	LOL-ACC-0407
Application	Accent
Name	Pole or Surface Mounted Accent

Description

The LOL-ACC-0407 is designed to be mounted on horizontal or vertical surfaces. It has a fully adjustable head allowing 360° rotation and 0-20° elevation.

Power Input	Remote driver, Series
Lamp details	LED Module
Power Usage	60W
Beam Angles	13, 22, 33
Colour Temperature	2700k, 3000k, 4000k
Lumen	5000lm@1400mA
CRI	80+, 90+
Dimming System	DALI, 0-10 Volt

IP

Finish	Black/ White/ Grey Powdercoat on aluminium, other Colours Available
---------------	---------------------------------------------------------------------------

Mounting	Variable Length Pole Mount or Surface Mount. Optional flange or set directly in concrete (pole mount) or stainless steel
-----------------	-----------------------------------------------------------------------------------------------------------------------------------

Dimensions	Type 1&2 Light: 126Ø x 110H, Type 1&2 Pole: 90Ø x 150-2000H, Type 3 Light: 126Ø x 110H, Type 3 Base: 127Ø x 80L, Flange: 250Ø
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------

Product Notes

* integral 240V driver or an external remote driver.** 90+ CRI Option

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

