

LOL-ACC-0462

Application Accent	
Name Spot Light on Arm	1

Description

When installed horizontally, the LOL-ACC-0462 will throw light either back onto exterior wall features such as signs, architectural details etc, or down onto the ground below. It is suitable for mounting on masonry, stone or timber facades and the head will clear most wall creepers. Or it can be mounted onto a horizontal bench top as a BBQ light. It allows full 360° rotation with 0-90° elevation for accurate targeting of features to be lit.

Power Input	12V AC, 24V DC, 240V
Lamp details	MR16, GU10
Power Usage	4W-6W
Beam Angles	15, 25, 38
Colour Temperature	2700k, 3000k (90+ option)
Lumen	600 lm
CRI	85+, (90+ option)
Dimming System	
IP	IP66
Finish	Black/ Bronze/ White & Other Colours Powdercoat on aluminium
Mounting	Surface mount stainless steel screws
Dimensions	78Ø x 156H x 528L

Product Notes

Wall mount 2.4m from ground. Low glare accessories: snoot, glare guard, hex cell louvre screen, or locking knuckle options available. Shorter custom lengths available.

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

