

### LOL-ACC-1066

<b>Model No</b>	LOL-ACC-1066
<b>Application</b>	Accent
<b>Name</b>	High Output Low Voltage Accent
<b>Description</b>	
<p>The LOL-ACC-1066 is a high-output accent designed for architectural and commercial lighting applications. Available in White or RGBW options with advanced colour mixing optics, the LOL-ACC-1066 is perfect for the dynamic RGB illumination of a variety of external facades and features.</p>	
<b>Power Input</b>	24V DC
<b>Lamp details</b>	LED Module
<b>Power Usage</b>	20W
<b>Beam Angles</b>	10, 35, 55
<b>Colour Temperature</b>	2700k, 3000k, RGBW
<b>Lumen</b>	2284 lm, 2380 lm
<b>CRI</b>	90+
<b>Dimming System</b>	Call to discuss
<b>IP</b>	IP67
<b>Finish</b>	Black/ Bronze/ Powdercoat on Aluminium
<b>Mounting</b>	Surface or Spike Mount Option
<b>Dimensions</b>	75Ø x 140L x 87D
<b>Product Notes</b>	
Other colours available, please contact us to discuss	

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

