

LOL-DOW-0156

Model No	LOL-DOW-0156
Application	Downlight
Name	Hanging light
Description	<i>This low voltage hanging light is perfect for lighting pergolas and arbors. It is constructed of heavy-gauge extruded solid copper tubing and a precision CNC-machined solid brass base. The housing is fitted with dual silicone o-ring gaskets to ensure a superior weather-tight seal. A tempered shock and heat resistant soda-lime glass lens safeguards the lamp and optics. A solid brass loop with a 2m stainless steel cable-hanger is also included.</i>
Power Input	12V
Lamp details	MR16
Power Usage	4W-7W
Beam Angles	Narrow, Medium, Wide
Colour Temperature	2950k
Lumen	389 lm - 550 lm
CRI	80+, 90+
Dimming System	Available depending on lamp
IP	
Finish	Brushed Copper
Mounting	Hanging with stainless steel cable and brass loop provided
Dimensions	118H x 54Ø
Product Notes	Clear or frosted glass lens available

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

