

LOL-DOW-0209

<b>Model No</b>	LOL-DOW-0209
<b>Application</b>	Downlight
<b>Name</b>	Water resistant ceiling down light

#### Description

*This water resistant luminaire is machined from a choice of solid aluminium with a UV stable powder coated finish or solid copper or 316 stainless steel. It comes with a clear\* or tempered or flush glass lens and high temperature silicon gaskets.*

<b>Power Input</b>	12V, 240V
<b>Lamp details</b>	MR16, GU10
<b>Power Usage</b>	4W-7W
<b>Beam Angles</b>	15, 25, 38, 60
<b>Colour Temperature</b>	2700k, 3000k
<b>Lumen</b>	TBA
<b>CRI</b>	90+
<b>Dimming System</b>	0-10 Volt, DALI Interface
<b>IP</b>	IP66
<b>Finish</b>	Varied Colours Powdercoated Aluminium, Copper, 316 Stainless Steel

<b>Mounting</b>	3 Bolt Internal Flange
-----------------	------------------------

<b>Dimensions</b>	Type 1 (MR16): 107H x 64Ø, Type 2 (GU10): 125H x 64Ø
-------------------	---

#### Product Notes

Frosted lens, hex cell louvre, glare guard and snoot available.

#### General Notes

*Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.*

#### Installation

*Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.*

