

LOL-DOW-0388

Model No	LOL-DOW-0388
Application	Downlight
Name	Mini Handrail Light
Description	<i>The LOL-DOW-0388 is suitable for public and domestic installations. It accommodates a wide range of options of beams, CCT and colours. The LOL-DOW-0388 is powerful, yet small and unobtrusive, theft and vandal resistant, so it is very suitable for any public setting.</i>
Power Input	500mA
Lamp details	LED Module
Power Usage	1.4W
Beam Angles	70, 75
Colour Temperature	2700k, 3000k, 4000k
Lumen	170 lm - 180 lm
CRI	80+, 90+
Dimming System	0-10 Volt Available on application
IP	IP65, IP68 option
Finish	Electroplated 316 Stainless Steel
Mounting	Recessed, proprietry installation tool required. 1.5mm minimum wall thickness
Dimensions	Type 1 & 2: 16Ø x 15H
Product Notes	*other colours available including RGB ** Beam:70deg - standard, minimal light spill 75deg- vertical asymmetric, 70deg - vertical symmetric, suitable for mid-rails*** IP68 if a borosilicate lens is specified

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.





Installation examples as downlight and handrail light




Type 1
Curved face suitable for Ø35 - Ø100 handrail





Type 2
Flat face suitable for flat surface metal handrail






Asymmetric 70 degrees



Asymmetric 75 degrees



Symmetric 70 degrees



Type 1

Type 2