

### LOL-DOW-0458

<b>Model No</b>	LOL-DOW-0458
<b>Application</b>	Downlight
<b>Name</b>	Mini Surface Mount Downlight
<b>Description</b>	The LOL-DOW-0458 is a stylish mini luminaire in either a cube or cylinder form. The body made from aluminium and it has a good IP rating.
<b>Power Input</b>	350mA Remote driver
<b>Lamp details</b>	LED Module
<b>Power Usage</b>	1.5W (Type 1 & 4), 2W (Type 2 & 5), 6.5W (Type 3 & 6)
<b>Beam Angles</b>	32 (Type 1 & 4), 47 (Type 2 & 5), 62 (Type 3 & 6)
<b>Colour Temperature</b>	3000k
<b>Lumen</b>	170 lm (Type 1 & 4), 225 lm (Type 2 & 5), 705 lm (Type 3 & 6)
<b>CRI</b>	85+
<b>Dimming System</b>	0-10 Volt, DALI Interface, Phase
<b>IP</b>	
<b>Finish</b>	Black/ White Powdercoat on Aluminium
<b>Mounting</b>	Surface Mount
<b>Dimensions</b>	Type 1: 25W x 25D x 25H, Type 2: 35W x 35D x 35H, Type 3: 45W x 45D x 45H, Type 4: 25Ø x 37H, Type 5: 35Ø x 37H, Type 6: 45Ø x 47H
<b>Product Notes</b>	

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation







Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.



Type 3



Type 6



Type 1-3

Type 4-6