



LOL-DOW-1238

Model No	LOL-DOW-1238
Application	Downlight
Name	Half Translucent Pendant Light
Description	
	elegant and durable solution to las or wherever a soft illumination
Power Input	12V AC, 24V DC
Lamp details	MR16
Power Usage	varies with lamp, 3W to 7W
Beam Angles	varies with lamp, 10 to 120 degrees
Colour Temperature	varies with lamp, 2700k to 4000k
Lumen	varies with lamp
CRI	varies with lamp, 80+ - 90+
Dimming System	
IP	
Finish	Translucent pearl and Copper, Brass, Black Brass
Mounting	Suspend from secure stainless steel eye bolt- not supplied
Dimensions	57Ø x 188H
Product Notes	
Ensure manufacturer's instructions are followed for installation. Recommended installation height at least 2.4M	

General Notes

above ground level.

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

