



LOL-DOW-7009

Model No	LOL-DOW-7009
Application	Downlight
Name	Indoor Mini Downlight Multiple Mount Options
Description	
This little downlight offers and installation options to	s a dazzling array of optics, finish o the designer.
Power Input	24V DC
Lamp details	LED Module
Power Usage	6W
Beam Angles	15, 20, 30, 40, 45x2
Colour Temperature	2700k, 3000k
Lumen	425 lm, 450 lm
CRI	90+
Dimming System	Mains dimming call to discuss
IP	IP20
Finish	Black Powdercoat Aluminium, Bronze, White, Champagne
Mounting	
Dimensions	Type 1: 38Ø x 71H x 0-2500D, Type 2: 38Ø x 86H x 0-2500D, Trimless: 39Ø x 39W x 41D, With Trim: 39Ø x tbaW x 41D, Remote: 58Ø x 35H, Integral: 58Ø x 75H
-	

Product Notes

Driver must be installed remotely for ceiling recessed mount as it will not fit through cutout hole.

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

