



LOL-ING-0282

Model No	LOL-ING-0282
Application	Inground
Name	Mini Symmetrical Recessed Uplight
Description	
	igh quality and practical luminaire . A square face plate option is
Power Input	350mA - Constant Current
Lamp details	LED Module
Power Usage	1W
Beam Angles	15, 30, 53
Colour Temperature	2700k, 3000k
Lumen	80lm
CRI	90+
Dimming System	
IP	IP68
Finish	Natural Copper, Anodised Aluminium, 316 Stainless Steel
Mounting	Ensure adequte drainage around light. Requires 40mm grey conduit except for timber decking.
Dimensions	Type 1: 43Ø x 39D x 4H, Type 2: 42Sq x 39D x 4H, Canister. 40Ø x 200D

^{*} remote driver required for 350mA constant current ** hex cell baffle available

IP68	Joining Kit	YES

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

