

LOL-ING-0288

Model No	LOL-ING-0288
Application	Inground
Name	Symmetrical Recessed Uplight
Description	The LOL-ING-0288 is a high quality and practical luminaire with contemporary styling.
Power Input	12V AC, 24V DC, 700mA Constant Remote
Lamp details	LED Module
Power Usage	2W, 4W
Beam Angles	26, 36, 74
Colour Temperature	2700k, 3000k
Lumen	170lm, 340 lm
CRI	90+
Dimming System	
IP	IP68
Finish	Natural Copper, 316 Stainless Steel, Powdercoated Aluminium
Mounting	Installation in soil or concrete requires 50mm conduit.
Dimensions	Type 1: 58Ø x 62D x 4H, Type 2: 75Ø x 62D x 4H, Type 3: 53Sq x 62D x 4H, Type 3: 61Sq x 62D x 4H, Canister: 50Ø x 200L

Product Notes

* Connect remote driver versions in series and integral driver versions in parallel ** hex cell baffle available

IP68 Joining Kit YES

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

