

### LOL-ING-1067

<b>Model No</b>	LOL-ING-1067
<b>Application</b>	Inground
<b>Name</b>	High Output Inground Light
<b>Description</b>	<i>The LOL-ING-1067 is a high-powered recessed uplight for illuminating walls, features and columns. Available with advanced wall-washing reflector for even horizontal illumination and glare minimization, the LOL-ING-1067 can also be configured with triple TIR options for symmetric beam patterns and RGBW operation.</i>
<b>Power Input</b>	24V DC
<b>Lamp details</b>	LED Module
<b>Power Usage</b>	30W
<b>Beam Angles</b>	10, 25, 35
<b>Colour Temperature</b>	3000k, RGBW
<b>Lumen</b>	1800 lm
<b>CRI</b>	90+
<b>Dimming System</b>	please call to discuss
<b>IP</b>	IP67
<b>Finish</b>	Black, Bronze Machined Aluminium
<b>Mounting</b>	Inground. Ensure adequate drainage around light.
<b>Dimensions</b>	Light: 180Ø x 64H, Canister: 157Ø x 70H
<b>Product Notes</b>	Drill 160mm DIA x 75mm deep hole for canister
<b>IP68 Joining Kit</b>	YES

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.



Light and Canister

