

LOL-ING-1074

Model No	LOL-ING-1074
Application	Inground
Name	Mini Uplighter
Description	<p>The LOL-ING-1074 can be used in many areas where either discreet or highly visible path marker lighting is required. The body is hard wearing CNC machine marine grade aluminum or brass. The optics provide a wide range of choices making this uplight useful in many different exterior settings.</p>
Power Input	24V DC - 3 wire
Lamp details	LED Module
Power Usage	2W
Beam Angles	15, 30, 50, 70
Colour Temperature	2700k, 3000k, 5700k, RGB
Lumen	150 lm, 80 lm RGB
CRI	tba
Dimming System	3 wire PWM
IP	IP67
Finish	Machined Brass, Black Powdercoat Aluminium, Silver Brushed Aluminium, White or Custom Colours Powdercoat Aluminium
Mounting	Recessed with canister for concrete or masonry. 18mm cutout hole
Dimensions	25Ø x 65H
Product Notes	
IP68 Joining Kit	YES
General Notes	<p>Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.</p>
Installation	<p>Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.</p>

