

LOL-ING-1098

|                           |   |
|---------------------------|---|
| <b>Model No</b>           | LOL-ING-1098  |
| <b>Application</b>        | Inground  |
| <b>Name</b>               | High Output Mid Height Light  |
| <b>Description</b>        | The LOL-ING-1098 is designed for lighting medium height facade and other architectural structures. It will deliver a high lumen output in four beam angle options ranging from narrow to medium width. An asymmetric wash option is also available. |
| <b>Power Input</b>        | 24V DC  |
| <b>Lamp details</b>       | LED Module  |
| <b>Power Usage</b>        | 15W   |
| <b>Beam Angles</b>        | 10, 20, 30, 40, Assymetric wash   |
| <b>Colour Temperature</b> | 3000k   |
| <b>Lumen</b>              | 1500 lm   |
| <b>CRI</b>                | 90+   |
| <b>Dimming System</b>     |   |
| <b>IP</b>                 | IP67  |
| <b>Finish</b>             | Black, Bronze, White, Silver Powdercoat Aluminium   |
| <b>Mounting</b>           | Inground, ensure adequate drainage around light.  |
| <b>Dimensions</b>         | 120Ø x 70H  |
| <b>Product Notes</b>      | Special coastal finish available for coastal locations  |
| <b>IP68 Joining Kit</b>   | YES   |

### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

