

### LOL-ING-1116

<b>Model No</b>	LOL-ING-1116
<b>Application</b>	Inground
<b>Name</b>	Compact Inground
<b>Description</b>	The LOL-ING-1116 fixture comes with 3 different beam spread optics (15, 30 & 60) and a hex cell glare control, to help create perfect illumination in many different locations. Machined from solid brass.
<b>Power Input</b>	12V AC
<b>Lamp details</b>	LED Module
<b>Power Usage</b>	3W
<b>Beam Angles</b>	15, 30, 60
<b>Colour Temperature</b>	2700k, 3000k
<b>Lumen</b>	180 lm
<b>CRI</b>	90+
<b>Dimming System</b>	Call to discuss
<b>IP</b>	
<b>Finish</b>	Black, Nickel, Brushed Brass
<b>Mounting</b>	Recessed, install in conduit
<b>Dimensions</b>	38Ø x 68D x 2H
<b>Product Notes</b>	Allow for conduit (25mm inside diameter) for cutouts.
<b>IP68 Joining Kit</b>	YES

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

