

### LOL-ING-1360

**Model No** LOL-ING-1360

**Application** Inground

**Name** Dark Lighter

#### Description

The LOL-ING-1360 can be used as an uplight, downlight or recessed into a wall to provide a focussed beam of light wherever a small focused area of illumination is needed. The low profile and excellent glare reduction properties of the LOL-ING-1360 makes it useful in high traffic areas.

**Power Input** 12V AC, 700mA - Series  
Wired, 24V DC

**Lamp details** LED Module

**Power Usage** 2W

**Beam Angles** 26

**Colour Temperature** 2700k, 3000k, 4000k

**Lumen** 170 lm

**CRI** 90+

#### Dimming System

#### IP

**Finish** Copper, 316 Stainless Steel,  
Black/White/Bronze  
Powdercoat on Aluminium

**Mounting** Drill 51mm x 200mm deep hole  
for cannister. Ensure adequate  
drainage around light.

**Dimensions** 58Ø x 87D x 41W x 3.5H

#### Product Notes

75mm diameter, wide flange option available. Hex baffle option, as shown in photo, is recommended to help eliminate glare. Load rated up to 5000kg

**IP68 Joining Kit** YES

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

