

LOL-PAT-0044

| Model No | LOL-PAT-0044 |
|-------------|---------------------------|
| Application | Path or Step |
| Name | Classic Eyelid Step Light |
| Description | |

The LOL-PAT-0044 is designed for recessed mounting into masonry, stone or wood, lighting exterior steps, paths and paved areas. The eyelid masks the light source, providing excellent glare-reduced illumination.

| oxoononi giaro rodacca ii | idiffiifidatioff. |
|---------------------------|--|
| Power Input | 12V, 24V AC/DC |
| Lamp details | MR16 |
| Power Usage | 4W-6W |
| Beam Angles | 15, 25, 38, 60 |
| Colour Temperature | 2700k, 3000k |
| Lumen | 420 lm - 600 lm |
| CRI | 90+ |
| Dimming System | |
| IP | IP67 |
| Finish | Copper, 316 Stainless Steel, Bronze, White or Black Powdercoat Aluminium |
| Mounting | Recessed with proprietary canister |
| Dimensions | Canister: 76Ø x 145L, Step light: 88Ø x 93L x 33D |
| | |

General Notes

Product Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.


Hex cell louvre for further glare reduction option available

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.



Stainless Steel





Copper after exposure to weather

