

### LOL-PAT-0290

<b>Model No</b>	LOL-PAT-0290
<b>Application</b>	Path or Step
<b>Name</b>	Single or Twin Post Light
<b>Description</b>	The LOL-PAT-0290 has one or two spotlights connected to a fully adjustable arm allowing 360 degree rotation and 0-90 degree elevation. It is ideal for path lighting as well as tree lighting. The head may be aimed downwards to eliminate vertical light.
<b>Power Input</b>	12V AC\DC, 24V AC\DC
<b>Lamp details</b>	LED Module, MR16
<b>Power Usage</b>	6W, 12W
<b>Beam Angles</b>	15, 25, 38, 60
<b>Colour Temperature</b>	2700k, 3000k, 4000k
<b>Lumen</b>	600, 1200
<b>CRI</b>	90+
<b>Dimming System</b>	
<b>IP</b>	
<b>Finish</b>	Bronze, Copper, 316 Stainless Steel, Variety of Powdercoat colours
<b>Mounting</b>	Spike mount
<b>Dimensions</b>	Type 1 Single: 64Ø x 144L x 820H, Type 2 Double: 64Ø x 262L x 820H

#### Product Notes

Retro option in pole base available in both single and twin versions in either powdercoated aluminium or copper or stainless steel.

#### General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

#### Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

