



LOL-PAT-1028

Model No	LOL-PAT-1028
Application	Path or Step
Name	Assorted Low Glare Bollards
Description	
	n minimal contemporary aesthetic architectural settings. Best suited reways and pathways.
Power Input	240V, 700mA - Series Wired, 24V DC
Lamp details	LED Module
Power Usage	26W
Beam Angles	Refer to Optic
Colour Temperature	2700k, 3000k
Lumen	100 lm
CRI	80+
Dimming System	
IP	
Finish	Black, White, Grey, Bronze, Silver, Olive Green, Corten
Mounting	Direct Burial (DB) or Flange (FL)
Dimensions	Type 1 FL: 1000H x 100W x 250L, Type 1 DB: 1200H x 100W x 150L, Type 2 FL: 1000H x 100W x 250L, Type 2 DB: 1200H x 100W x 160L, Type 3 FL: 1000H x 115W x 250L, Type 3 DB: 1200H x 115W x 185L
Product Notes	
CRI 90 option	

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

