

LOL-WAL-0052

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No | LOL-WAL-0052 |
| Application | Wall |
| Name | Up Down Wall Light |
| Description | The LOL-WAL-0052 illuminates both upwards and downwards giving columns or gateway pillars or entrances a dramatic effect. The 240V option allows for TPS cable connection. |
| Power Input | 12V, 240V |
| Lamp details | LED MR16, GU10 |
| Power Usage | 4W-7W x2 |
| Beam Angles | 15, 25, 38, 60 |
| Colour Temperature | 3000k, 4000k |
| Lumen | 550 lm |
| CRI | 85+ |
| Dimming System | 0-10 Volt, DALI Interface, - Phase |
| IP | |
| Finish | Solid Copper, 316 Stainless Steel, Aluminium Powdercoat various |
| Mounting | Surface Mount |
| Dimensions | 240V Back Plate: 100L x 78Ø x 141H, 12V Back Plate: 96L x 78Ø x 141H |
| Product Notes | *Long Snoot option available **Glare guard option available ***Hex cell louvre guard option available ****Diffusing Snoot option available |

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.

