



LOL-WAL-0062

Model No	LOL-WAL-0062
Application	Wall
Name	Surface Mounted Downlight
Description	

The LOL-WAL-0062 is suitable for mounting on timber masonry stone etc. non-adjustable for one way wall washing. It can be mounted with the lamp directed up or down. Body and base CNC machined or hand spun from either Aluminium or Copper or Stainless Steel.

Power Input	12V AC, 240V
Lamp details	LED Module
Power Usage	4W-7W
Beam Angles	15, 25, 38, 60
Colour Temperature	3000k
Lumen	600lm

90+

CRI

IP			

Finish	Stainless Steel, Copper, Powdercoat Aluminium	
Mounting	Surface mount with back plate	
Dimensions	100L x 78Ø x 90H	

Product Notes



Hedge Uplight Installation Option



Downlights with Glare Guards Installation Option

General Notes

Please contact Light on Landscape to confirm the availability and current specifications of this luminaire.

Installation

Light on Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joins, heat shrink connectors and quality lamps.